



# ANTICANTE PLUS

## ACIDIC BASED SOLUTION FOR THE “ANTIQUE” PROCESS OF MARBLE SURFACES

### Description:

Product based on inhibited acids formulated for the treatment of polished, saw faced, tumbled, honed and brushed marble or for materials containing calcium carbonate such as ROSSO VERONA, TRANI, BIANCONE, BOTTICINO, GIALLO D'ISTRIA, LIMESTONES, TRAVERTINE and CARRARA etc to give a chemical antique finish, consumed or a orange peel finish to the material. Depending on the hardness and type of the material one application is sufficient. Ideal product for stone masons and applicators to avoid a mechanical antique process of material.

### How to use:

Before proceeding with application of ANTICANTE PLUS, make sure material and surface is clean and dry. (remove all surface debris and previous wax, ingrain dirt and grime and adhesive or cement based residues so to obtain a uniform and effective application). Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is corrosive.

ANTICANTE PLUS is applied directly on the material to be treated in a uniform manner and spread over surface using appropriate applicator and left in contact with surface for approximately 15 minutes or until the chemical reaction is exhausted. Once obtained the desired finish, rinse surface with clean water and remove all access residues. If used on existing floor surfaces removed all residues using a solution of the product DETERMAC diluted in water at 5%.

### Maintenance:

Daily maintenance of treated surface can be carried out using our product DETERCLEANER diluted in water as indicated on technical data sheet. For periodic maintenance of treated surfaces, clean with DETERMAC diluted in water using a ratio of 1:9

### Notes:

Our technical office is available for any technical support regarding product application and if needed we can recommend qualified technical teams for product application.

### Coverage:

1 to 2 m<sup>2</sup> with one liter of product

### Packaging:

5000 ml containers available in boxes of 4 pieces - 10 l. and 60 l. containers available on request. Product subject to ADR regulations.

*Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.*