



CONSOLIDANTE

WATER REPELLENT, CONSOLIDATING TREATMENT FOR MARBLES AND SANDSTONE

Description:

CONSOLIDANTE is a mixture of resins and solvents formulated to be applied to old, soft, powdering or deteriorating masonry, marble, sandstone terracotta or natural stone surfaces with the objective to bind together the stones particles creating a stronger and more resistant surface. Based on formulation, product will penetrate deeply inside material protecting also from water and moisture which over time creates a breakdown of stone surface. Treated surface will maintain their original aspect, long lasting and UV resistant.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10° C

Apply CONSOLIDANTE by brush or spray uniformly to on a clean and dry surface, making sure to remove excess product or avoid product drips on vertical applications. Repeat applications with cycles of 30/40 minutes between each application until complete surface saturation.

Maintenance:

n.a.

Notes:

n.a.

Coverage:

Based on type of material and porosity, 1lt of product will cover from 2 up to 3m2. On low absorbing materials the coverage can be from 6 to 10 m2 per 1lt.

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.