



DERUGGINE

ACIDIC BASED RUST REMOVER

Description:

Mild acidic based detergent for the removal of rust and oxidation from natural and on polished natural stone. DERUGGINE is effective on all materials such as Beola, Quarzites, Serizzo and those materials which contain a high amount of ferrous minerals which in the presence of humidity and moisture, tend to oxidize leading to the formation of yellow or rust marks. Product can be used internally and externally or within the production phase to remove rust marks caused by metallic shavings or machinery. DO NOT USE ON POLISHED MARBLE SURFACES.

How to use:

Before proceeding with application of DERUGGINE protect and cover all surroundings, plants and wall surfaces and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing).

Pre wet surface before proceeding with DERUGGINE. Apply a prepared solution of DERUGGINE evenly on surface to be cleaned allowing a contact time of 2/3 minutes. before proceeding to scrub surface using a mono brush (155-175 rpm) and soft bristled pad. Rinse surface using a solution of DETERMAC diluted in water at 5% and remove all residues using a wet vacuum.

Note: do not allow product to dry on surface and do not walk on surface during product application. Surface can be used once all product is removed and cleaned.

Dilution rates:

Light cleaning: dilute in water using a ratio of 1:10
Standard cleaning: dilute in water using a ratio of 1:4
Deep cleaning: dilute in water using a ratio of 1:1
Extreme: product can be used pure.

Notes:

-

Coverage:

4 to 6 m² with one liter of product

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.