



G1 POWDER

PROFESSIONAL POLISHING POWDER FOR GRANITES AND RESIN QUARTZ

Description:

G1 POWDER is professional polishing powder specific for granite and resin base agglomerate surfaces, to obtain a natural flat high gloss surface. G1 POWDER can be used on a dull worn down granite surfaces to obtain a renewed high shine surface or can be inserted into a maintenance cycle to maintain surface gloss. Product can be used in a restoration process following a traditional mechanical grinding process from a 1200/1500 grit saving time and money on jobsite. Product will remove light surface scratches and will not leave surface residues or films on surface. Highly recommended on granite surfaces in high traffic areas such as hotel lobbies, shopping centers, commercial buildings and residential surfaces.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Do not apply where temperatures are below 5 °C – Work product to a maximum of 1m2 at a time. Apply a clean and dry surface.

Apply a 30/60 gr of product or a s of product to area to be polished. Add water so to create a thick creamy paste. Proceed to polish area using a mono brush (155 rpm) and white felt pad in small areas until desired gloss is obtained. (needed approximately 10 passes with machine). Check regularly using a squeegee during process until result is obtained. Do not allow product to dry out. Add water to creamy paste if needed or product is drying out.

Remove all sludge and rinse surface with clean water. Wet vacuum all residues.

Maintenance:

Treated surface can be cleaned daily using our neutral universal detergent DETERCLEANER with a traditional wet mop process or scrubber dryer.

Notes:

n.a.

Coverage:

Depending on where product is used, 1kg of product will polish up to 100 m2;
Surface Restoration: 1kg up to 50 m2 (30/60 gr)
Surface Maintenance: 1kg up to 100 m2 (10/20 gr)

Packaging:

Tubs of 5kg – 25kg

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.