



# PREFUGA

## WATER BASED, PRE GROUTING, PROTECTIVE TREATMENT

### Description:

PREFUGA is protective water based formulation used as a grout release protecting the tile or material from staining when using coloured grouts or cement based adhesives. Treatment is applied before grouting and will protect material from eventual installation dirt and grime and allowing the grout clean up to be easier and quicker. Highly recommended on all porous stone surfaces such as natural stone, limes tone, terracotta to avoid grout penetrating in micro pores becoming difficult to remove. Product is compatible with damp surfaces and can be applied on both internal and external applications.

### How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Do not apply where temperatures are below 10°C

Apply two coats of PREFUGA by brush or spray uniformly to surface with 3-4 hours between each application. Product will cure completely after 8-12 hours.

For the cleanup of grout residues we recommend using our DETERCANTIERE diluted in water as of instructions. Once clean up has been completed, we highly suggest that material is protected using a appropriate protective treatment.

### Maintenance:

n.a.

### Notes:

n.a.

### Coverage:

Based on type of material and porosity, 1lt of product will cover from 12 up to 15m2. . On compact surfaces, treatment can cover up to 20 m2

### Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

*Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.*