



# RIPARA FUGA

## SOLVENT BASED, PROTECTIVE, ANTI-FILTRATION TREATMENT FOR EXTERNAL TILED TERRACES

### Description:

RIPARA FUGA is a ethyl silicate based formulation created for the water repellent protection of horizontal surfaces which have micro hairline cracks up to 1.5mm where water filtration over time causes the substrate to deteriorate and the potential growth of algae and mould. RIPARAFUGA will protect deeply and create a micro barrier on surface and in joints so to avoid all water absorption and potential structure issues due to moisture and presence of humidity. For external application.

### How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Do not apply where temperatures are below 10°C

Apply RIPARA FUGA by brush or spray uniformly to on a clean and dry surface, making sure complete penetration in all surface cracks and joints. Remove excess product after 15 – 20 minutes using a clean cloth dampened with white spirits. Protect surfaces for a period of 24 hours from rain and water until to allow complete product curing.

### Maintenance:

n.a.

### Notes:

n.a.

### Coverage:

Based on type of material and porosity, 1lt of product will cover from 10 up to 30m<sup>2</sup>.

### Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

*Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.*