



ZEUS AQ

SUPREME, HIGH PERFORMANCE, WATER BASED ANTI STAIN SOLUTION FOR ALL SURFACES

Description:

Supreme formulation, high performance, universal, protective anti stain treatment for all stone, marble and granite materials used on flooring, worktops, bathrooms, wet rooms or on any cut to size project. Product blocks rising humidity and moisture when applied to material before installation and is highly recommend in areas to block staining and marking from food staining, dirt and grime, yellowing, oxidations, and smog. Based on its formulation of prime raw materials, ZEUS AQ does not change the natural color of material or leave surface films. Product is odorless and non yellowing. ZEUS AQ can be applied to all polished and non polished stone surfaces such as marbles, granites, limestone's, quartzite's, terrazzo, terracotta, cement, agglomerates and much more. Breathable and UV resistant.

How to use:

Always test product first before proceeding with complete product application in order to determine final finish and products compatibility with material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10° C

Always apply to dry and clean surfaces. Apply ZEUS AQ uniformly by low pressure spray, cloth or brush to surface to be treated. Allow product penetration inside material before removing any excess product residue from surface by cloth. Dry excess can be removed using a white felt pad. Allow a complete curing time of surface for 12/24 hours for complete surface protection.

Maintenance:

ZEUS AQ is compatible with surface waxes and treatments. For daily cleaning of treated surface with recommend using our product DETERCLEANER diluted in water as indicated in TDS. For periodic or extraordinary cleaning cycles, please proceed and clean treated surface using DETERMAC diluted as indicated on TDS.

Notes:

n.a.

Coverage:

Based on type of material and porosity, 1lt of product will cover from 5 up to 25m2.

Packaging:

1000 ml bottles available in boxes of 10 pieces - 5000 ml containers available in boxes of 2 pieces - 10 l. and 60 l. containers available on request

Whoever before using this product, should fully read completely the product label, the technical data sheet and material safety data sheet or contact us directly for any information. We highly recommend to follow precisely all indications within supplied documentation. We highly recommend that the product is always tested first in a inconspicuous area so to determine the products compatibility and final result with the material to be treated. In all cases please maintain packaging tightly closed and always out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.